ProductSheet

HP Z24q G3 QHD Display (4Q8N4AA)

The Ideal Space to Create



The Z24q G3 displays professional grade color and design optimized for hybrid or office work. Bring your ideas to life with industry-leading color accuracy and HDR 400 or take advantage the pixel dense QHD 23.8-inch screen—perfect for creating wherever your desk may be.



Closing the Gap Between Screen and Reality

Trust the colors you see on screen with the world class Z by HP color accuracy you expect. Equipped with the creative color gamuts you work in most, you'll have all the shades and hues you need for web, photography, and video creation on Mac® or PC. Lean into realism with HDR 400 for darker blacks and brighter whites.

Stunning Detail. Smoother Performance.

Experience every pixel and movement with the precision of reality in crisp QHD resolution and a fast 90hz refresh rate[1]. Navigate your workflow in Windows 11 and Adobe® with high definition and smooth motion as you scroll, click, and direct your projects.

Expand Your Canvas

Finally, a display just as resourceful as you. Make the most of your desk and upgrade your virtual meetings by connecting your HP Z24m G3 display via daisy-chain with just one cable[8]. The razor-thin, frameless designs of both monitors match perfectly while maximizing your screen and integrating premier conferencing features.

Featuring

Colors Calibrated to Perfection

Every HP Z Display undergoes factory color calibration and testing to achieve a Delta E of less than 2, making color differences virtually indistinguishable to the human eye.

The Color Gamuts You Use Most

Create in the color gamuts you use most. 99% sRGB for web, 90% P3 for photography, and BT.709 for HD video.

Shine Brightly

With 400 nits of brightness, you can clearly see your screen when you're in the sun, by a bright window, or under artificial lighting. $^{[1]}$

Lean into Realism with HDR 400

Lean into realism with HDR 400 for deeper blacks, brighter whites, and richer colors.

Crisp QHD Resolution

See 2x the details on your 23.8-inch screen with crisp QHD resolution.

Specifications

Panel technology	Display size (diagonal)	23.8"
Display size (diagonal)		
Aspect ratio 16:9		
Native resolution		
Resolutions supported 640 x 480; 720 x 400; 800 x 600; 1024 x 768; 1280 x 720; 1280 x 1024; 1440 x 900; 1600 x 1200; 1680 x 1050; 1920 x 1080; 1920 x 1200; 2560 x 1400 Pixel pitch 0.21 x 0.21 m Brightness 400 nits ^[1] Contrast ratio 1000:1 ^{1]} Response time (typical) Minimum dimensions (W x D x H) 75.84 x 3.85 x 31.37 cm (Without stand.) Minimum dimensions (W x D x H) 72.12 x 15.25 x 12.35 in (Without stand.) Minimum dimensions (W x D x H) 73.84 x 19.5 x 48.93 cm Weight 4.8 kg (With stand.) Weight 10.6 ib (With stand.) Display features On-screen controls; Anti-glare; Height Adjust/Tilt/Swivel/Pivot; HP Eye Ease Onscreen controls Brightness; Color control; Contrast; Exit; image control; information; Language; Management; Power control; Input control Menu control Display scan frequency (horizontal) Display scan frequency (vertical) 50-90 Hz Camera No integrated camera Power 100 - 240 VAC 50/60 Hz Power consumption 74 W (maximum), 34 W (typical), 0.5 W (standby) Operating temperature range Sustainable impact specifications Maximum impact specifications Australian-New Zealand MEPs; Bis BSM; CB; CCC; CEC CECP; CEL; cTUVus; EAC; ENERGY STAR*; FCC; ISO 9241-307; CCC; CCC (CCC), CECP, CEL; cTUVus; EAC; ENERGY STAR*; FCC; ISO 9241-307; CCC, CCC, NOM, PSB; SEP	 	
Brightness 400 nits ^[1] 1000:1 ^[1] 100:1 ^[1] 1000:1 ^[1]		640 x 480; 720 x 400; 800 x 600; 1024 x 768; 1280 x 720; 1280 x 1024; 1440 x 900; 1600 x 900; 1600 x 1200; 1680
Contrast ratio 1000:1 ^[1] Response time (typical) 5m 6t6 (with overdrive) ^[1] Minimum dimensions (W x D x H) 53.84 x 3.85 x 31.37 cm (Without stand.) Minimum dimensions (W x D x H) 72.12 x 1.52 x 12.35 in (Without stand.) Dimensions With Stand (W x D x H) 53.84 x 3.95 x 48.93 cm Weight 4.8 kg (With stand.) Weight 0.0-10 ib (With stand.) Display features 0.0-s-creen controls; Anti-glare; Height Adjust/Tilt/Swivel/Pivot; HP Eye Ease Onscreen controls Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control (Input control; Menu control) Display colors Up to 1.07 billion colors supported (Input control; Menu control) Display scan frequency (vertical) 50-90 Hz Camera No integrated camera Power 100-240 VAC 50/60 Hz Power consumption 74 W (maximum), 34 W (typical), 0.5 W (standby) Operating temperature range 50 to 35°C Operating humidity range 20 to 80% non-condensing Sustainable impact specifications Sistainable impact specifications Certifications and compliances Certifications and compliances Physical security Security Lock-ready (Input control) (Input control); Input control; Information; Language; Management; Power control; Information; Language; Mana	Pixel pitch	0.21 x 0.21 mm
Response time (typical) Minimum dimensions (W x D x H) Minim	Brightness	400 nits ^[1]
Minimum dimensions (W x D x H) 53.84 x 3.85 x 31.37 cm (without stand.) Dimensions With Stand (W x D x H) 21.2 x 1.5 x 1.2 x 3.2 s in (without stand.) Dimensions With Stand (W x D x H) 48. kg (With stand.) Weight 10.6 lb (With stand.) Display features On-screen controls, Anti-glare; Height Adjust/Tilt/Swivel/Pivot; HP Eye Ease Onscreen controls Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control, Menu control Display scan frequency (norizontal) Display scan frequency (norizontal) On-240 VAC 50/60 Hz Camera No integrated camera Power 100 - 240 VAC 50/60 Hz Camera No integrated camera Power 100 - 240 VAC 50/60 Hz Camera No integrated camera No integrated camera No integrated camera No integrated camera No integrated camera No integrated camera No integrated ca	Contrast ratio	1000:1 ^[1]
Minimum dimensions (W x D x H) 2.1.2 x 1.5 x 1.5 x 1.2.35 in (Without stand.) Dimensions With Stand (W x D x H) 5.3.84 x 19.5 x 48.93 cm Weight Weight Weight 10.6 lb (With stand.) Display features On-screen controls; Anti-glare; Height Adjust/Tilt/Swivel/Pivot; HP Eye Ease Onscreen controls Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control Display colors Up to 1.07 billion colors supported (12) Display scan frequency (horizontal) Display scan frequency (vertical) Camera No integrated camera Power 100 - 240 VAC 50/60 Hz Power consumption 74 W (maximum), 34 W (typical), 0.5 W (standby) Operating temperature range Sustainable impact specifications 55% post-consumer recycled plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic Certifications and compliances Physical security Security lock-ready (2) Management Software HP Display Center; HP Display Manager UPC number Manufacturer Warranty Monitor; DisplayPort* cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup Weight With stand.) 21.2 1.2 1.2 1.2 1.2 1.2 1.2 1.3 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0	Response time (typical)	5ms GtG (with overdrive) ^[1]
Dimensions With Stand (W x D x H) 53.84 x 19.5 x 48.93 cm Weight 4.8 kg (With stand.) Weight 10.6 lb (With stand.) Display features 0n-screen controls; Anti-glare; Height Adjust/Tilt/Swivel/Pivot; HP Eye Ease Onscreen controls Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control Display scan frequency (horizontal) 30-140 KHz Display scan frequency (vertical) 50-90 Hz Camera No integrated camera Power 0100 - 240 VAC 50/60 Hz Power consumption 74 W (maximum), 34 W (typical), 0.5 W (standby) Operating temperature range 5 to 35°C Operating humidity range 20 to 80% non-condensing Sustainable impact specifications 85% post-consumer recycled plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; CTUYUS; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; NOM; PSB; SEPA; TCO Certified: TCO Certified Edge: TUY/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificates Physical security Security Incheredy I2 Management Software HP Display Center; HP Display Manager UPC number 39 each of the propertive cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup What's in the box What's in the box With Stand.) Weight (With stand.) Weight (With stand.) 10.6 lb	Minimum dimensions (W x D x H)	
Weight (With stand.) Weight (10.6 lb (With stand.) Display features On-screen controls; Anti-glare; Height Adjust/Tilt/Swivel/Pivot; HP Eye Ease Onscreen controls Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control; Menu control; Imput control; Menu control; Input control; Menu control; Input control; Menu control; Input control; Input control; Menu control; Information; Language; Management; Power control; Display scan frequency (Norizontal) Display scan frequency (Vertical) Display scan frequency (Vertical) So-90 Hz Camera No integrated camera Power 100 - 240 VAC 50/60 Hz Power consumption 74 W (maximum), 34 W (typical), 0.5 W (standby) Operating temperature range 5 to 35°C Operating humidity range 20 to 80% non-condensing Sustainable impact specifications 85% post-consumer recycled plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; cTUVus; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificates Physical security Security (Dck-ready ^[2] Management Software HP Display Center; HP Display Manager UPC number 196188122921 Manufacturer Warranty 3 year (3/3/0) limited warranty includes 3 years of parts and labor. No on-site repair. Terms and conditions vary by country. Certain restrictions and exclusions apply. What's in the box What's in the box Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup		(Without stand.)
Weight (With stand.) Display features On-screen controls; Anti-glare; Height Adjust/Tilt/Swivel/Pivot; HP Eye Ease Onscreen controls Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control Display colors Up to 1.07 billion colors supported ^[12] Display scan frequency (Norizontal) 30-140 KHz Camera No integrated camera Power 100 - 240 VAC 50/60 Hz Power consumption 74 W (maximum), 34 W (typical), 0.5 W (standby) Operating temperature range 5 to 35°C Operating humidity range 20 to 80% non-condensing Sustainable impact specifications 85% post-consumer recycled plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic Certifications and compliances (KC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificates Physical security Security Iock-ready. ^[2] Management Software HP Display Center; HP Display Manager UPC number 196188122921 Manufacturer Warranty Monitor; DisplayPort™ cable; UESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Dimensions With Stand (W x D x H)	53.84 x 19.5 x 48.93 cm
Display features On-screen controls; Anti-glare; Height Adjust/Tilt/Swivel/Pivot; HP Eye Ease Onscreen controls Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control Display colors Up to 1.07 billion colors supported ^[12] Display scan frequency (horizontal) Display scan frequency (vertical) So-90 Hz Camera No integrated camera Power 100 - 240 VAC 50/60 Hz Power consumption 74 W (maximum), 34 W (typical), 0.5 W (standby) Operating temperature range Operating humidity range 20 to 80% non-condensing Sustainable impact specifications 85% post-consumer recycled plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic Australian-New Zealand MEPS; BIS; BSM; CB; CCC; CE; CECP; CEL; CTUVus; EAC; ENERGY STAR®; FCC; ISO 9241-307; KCCC; MCCC; MOM; PSB; SEPA; TCO certified; TCO certified Edge; TUV/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificates Physical security Security lock-ready ^[2] Management Software UPC number 196188122921 Manufacturer Warranty Nonitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Weight	
Onscreen controls Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control Display colors Up to 1.07 billion colors supported ^[12] Josplay scan frequency (horizontal) Display scan frequency (vertical) 50-90 Hz Camera No integrated camera Power 100 - 240 VAC 50/60 Hz Power consumption 74 W (maximum), 34 W (typical), 0.5 W (standby) Operating temperature range 5 to 35°C Operating humidity range 20 to 80% non-condensing Sustainable impact specifications 85% post-consumer recycled plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; cTUVus; EAC; ENERGY STAR®, FCC; ISO 9241-307; KC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificates Physical security Security lock-ready ^[2] Management Software UPC number 196188122921 Manufacturer Warranty Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Weight	
Display colors Up to 1.07 billion colors supported [12] Display scan frequency (horizontal) Display scan frequency (vertical) Display scan frequency (vertical) So-90 Hz Camera No integrated camera Power 100 - 240 VAC 50/60 Hz Power consumption 74 W (maximum), 34 W (typical), 0.5 W (standby) Operating temperature range 5 to 35°C Operating humidity range 20 to 80% non-condensing Sustainable impact specifications 85% post-consumer recycled plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; cTUVus; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificates Physical security Security lock-ready ^[2] Management Software HP Display Center; HP Display Manager UPC number 3 year (3/3/0) limited warranty includes 3 years of parts and labor. No on-site repair. Terms and conditions vary by country. Certain restrictions and exclusions apply. What's in the box Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Display features	On-screen controls; Anti-glare; Height Adjust/Tilt/Swivel/Pivot; HP Eye Ease
Display scan frequency (horizontal) Display scan frequency (vertical) 50-90 Hz Camera No integrated camera Power 100 - 240 VAC 50/60 Hz Power consumption 74 W (maximum), 34 W (typical), 0.5 W (standby) Operating temperature range 5 to 35°C Operating humidity range 20 to 80% non-condensing Sustainable impact specifications 85% post-consumer recycled plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; cTUVus; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; TUV-5; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificates Physical security Security Iock-ready ^[2] Management Software HP Display Center; HP Display Manager UPC number 196188122921 Manufacturer Warranty 3 year (3/3/0) limited warranty includes 3 years of parts and labor. No on-site repair. Terms and conditions vary by country. Certain restrictions and exclusions apply. What's in the box Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Onscreen controls	
Display scan frequency (vertical) 50-90 Hz	Display colors	Up to 1.07 billion colors supported ^[12]
Power 100 - 240 VAC 50/60 Hz Power consumption 74 W (maximum), 34 W (typical), 0.5 W (standby) Operating temperature range 5 to 35°C Operating humidity range 20 to 80% non-condensing Sustainable impact specifications 85% post-consumer recycled plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; cTUVus; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificates Physical security Security Icck-ready ^[2] Management Software HP Display Center; HP Display Manager UPC number 196188122921 Manufacturer Warranty 3 year (3/3/0) limited warranty includes 3 years of parts and labor. No on-site repair. Terms and conditions vary by country. Certain restrictions and exclusions apply. What's in the box Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup		30-140 KHz
Power consumption 74 W (maximum), 34 W (typical), 0.5 W (standby) Operating temperature range 5 to 35°C Operating humidity range 20 to 80% non-condensing Sustainable impact specifications 85% post-consumer recycled plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic Certifications and compliances Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; cTUVus; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificates Physical security Security lock-ready ^[2] Management Software HP Display Center; HP Display Manager UPC number 196188122921 Manufacturer Warranty 3 year (3/3/0) limited warranty includes 3 years of parts and labor. No on-site repair. Terms and conditions vary by country. Certain restrictions and exclusions apply. What's in the box Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Display scan frequency (vertical)	50-90 Hz
Power consumption 74 W (maximum), 34 W (typical), 0.5 W (standby) Operating temperature range 5 to 35°C Operating humidity range 20 to 80% non-condensing Sustainable impact specifications Sustainable impact specifications Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; cTUVus; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificates Physical security Security lock-ready ^[2] Management Software HP Display Center; HP Display Manager UPC number 196188122921 Manufacturer Warranty Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Camera	No integrated camera
Operating temperature range 5 to 35°C Operating humidity range 20 to 80% non-condensing Sustainable impact specifications 85% post-consumer recycled plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic Certifications and compliances Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; cTUVus; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificates Physical security Security lock-ready ^[2] Management Software HP Display Center; HP Display Manager UPC number 196188122921 Manufacturer Warranty 3 year (3/3/0) limited warranty includes 3 years of parts and labor. No on-site repair. Terms and conditions vary by country. Certain restrictions and exclusions apply. Wharts in the boy Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Power	100 - 240 VAC 50/60 Hz
Operating humidity range 20 to 80% non-condensing Sustainable impact specifications 85% post-consumer recycled plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic Certifications and compliances Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; cTUVus; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificates Physical security Security lock-ready ^[2] Management Software HP Display Center; HP Display Manager UPC number 196188122921 Manufacturer Warranty 3 year (3/3/0) limited warranty includes 3 years of parts and labor. No on-site repair. Terms and conditions vary by country. Certain restrictions and exclusions apply. What's in the box Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Power consumption	74 W (maximum), 34 W (typical), 0.5 W (standby)
Sustainable impact specifications Sustainable impact specifications Restrictions and compliances Certifications and conditions vary includes 3 years of parts and labor. No on-site repair. Terms and conditions vary by country. Certain restrictions and exclusions apply. What's in the box Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Operating temperature range	5 to 35°C
Sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; cTUVus; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificates Physical security Security lock-ready ^[2] Management Software HP Display Center; HP Display Manager UPC number 196188122921 Manufacturer Warranty 3 year (3/3/0) limited warranty includes 3 years of parts and labor. No on-site repair. Terms and conditions vary by country. Certain restrictions and exclusions apply. What's in the box Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Operating humidity range	20 to 80% non-condensing
Certifications and compliancesKC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; South Africa Energy; ICE; UAE; Ukraine certificatesPhysical securitySecurity lock-ready [2]Management SoftwareHP Display Center; HP Display ManagerUPC number196188122921Manufacturer Warranty3 year (3/3/0) limited warranty includes 3 years of parts and labor. No on-site repair. Terms and conditions vary by country. Certain restrictions and exclusions apply.What's in the boxMonitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Sustainable impact specifications	
Management Software HP Display Center; HP Display Manager UPC number 196188122921 Manufacturer Warranty 3 year (3/3/0) limited warranty includes 3 years of parts and labor. No on-site repair. Terms and conditions vary by country. Certain restrictions and exclusions apply. What's in the box Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Certifications and compliances	KC/KCC; NOM; PSB; SEPA; TCO Certified; TCO Certified Edge; TUV/GS; TUV-S; VCCI; Vietnam MEPS; WEEE; ISC; Low
UPC number 196188122921 Manufacturer Warranty 3 year (3/3/0) limited warranty includes 3 years of parts and labor. No on-site repair. Terms and conditions vary by country. Certain restrictions and exclusions apply. What's in the box Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Physical security	Security lock-ready ^[2]
Manufacturer Warranty 3 year (3/3/0) limited warranty includes 3 years of parts and labor. No on-site repair. Terms and conditions vary by country. Certain restrictions and exclusions apply. What's in the box Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	Management Software	HP Display Center; HP Display Manager
country. Certain restrictions and exclusions apply. What's in the box Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; USB Type-A to B cable; Quick Setup	UPC number	196188122921
What's in the nev	Manufacturer Warranty	
	What's in the box	

Top Recommended Displays, Accessories and Services

Personal Systems Commercial Care Pack Services			
HP 4y Next Business Day Response Advanced Exchange Large DisplayHardware Support	U0J12E		
HP 5y Next Business Day Response Advanced Exchange Large DisplayHardware Support	U0J13E		

Messaging Footnotes

- [1] All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.
- [8] Not compatible with Mac products.

Technical Specifications Footnotes

- [1] All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.
- [2] Lock sold separately.
- [5] DisplayPort™ 1.2 or HDMI 1.4 required to drive panel at its native resolution. The video card of the connected PC must be capable of supporting 2560 x 1440 at 60 Hz with 10-bit color using one DisplayPort™, HDMI. The video card of the connected PC must be capable of supporting 2560 x 1440 and include one DisplayPort™ or one HDMI outputs to drive the monitor at the Preferred Mode.
- [11] Included cables may vary by country.
- [12] Number of colors through A-FRC technology.

Learn more at

hp.com

© Copyright 2022 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

DisplayPort[™] is a trademark owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. EPEAT® is a registered trademark of GREEN ELECTRONICS COUNCIL. Microsoft, Encarta, MSN, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

