



OWC Mercury Elite Pro Dual

Thunderbolt 2 | USB 3.1 Gen 1

Dual Drive Professional Hardware RAID

The next generation Mercury Elite Pro Dual with Thunderbolt 2 technology is the perfect RAID solution for creative workflows, project archives, and system backups where reliability and versatile performance count. An extreme performance Thunderbolt 2 interface and two drives, easily configured in multiple RAID modes, deliver speeds up to 474MB/s or mirrored data for peace of mind. It's the RAID workhorse for any environment — from large-scale, high demand production studios to your home office.

Key Features

- Nine capacity options up to 20TB
- Also available as an empty enclosure
- Maximize the potential of two 3.5" hard drives
- Configured in RAID 0 mode and available RAID 1, SPAN, or JBOD
- Speeds up to 474MB/s
- Thunderbolt 2 and USB 3.1 Gen 1 interface
- Heat-dissipating aluminum chassis with a variable-speed fan
- Drives included — 3 year OWC limited warranty
- Enclosure only — 1 year OWC limited warranty



OWC Mercury Elite Pro Dual

Tech Specs

Interface

- (2) Thunderbolt 2
- USB 3.1 Gen 1

Drives Supported

- (2) 3.5" SATA 6Gb/s drives

Hardware RAID Modes

- Preconfigured RAID 0
- RAID 1
- Span
- Independent

System Requirements

- Operating System
 - Thunderbolt 2
 - OS X 10.9.3 or later
 - Windows 7 or later
 - USB 3.1 Gen 1
 - OS X 10.6.8 or later
 - Windows XP or later

Power Supply

- External, UL-listed, universal auto-switching
- AC input: 100 ~ 240V, 50/60Hz
- DC output: 12V 6.0A

Data Transfer Rate

- Thunderbolt 2: Read: 474MB/s and Write: 474MB/s
- USB 3.1 Gen 1: Read: 416MB/s and Write: 393MB/s
- *Notes: Speeds will vary based on drives used, RAID configurations, and other factors*

Operating Environment

- Environmental (Non-Operating)
 - Temperature (°F): -40° to 149°
 - Temperature (°C): -40° to 65°
- Environmental (Operating)
 - Temperature (°F): 41° to 107°
 - Temperature (°C): 5° to 42°

Includes

- OWC Mercury Elite Pro Dual
- 1.0 m (39 in) Thunderbolt cable
- 0.6 m (24 in) USB 3.1 Gen 1 Standard-A to Standard-B cable
- External power supply and power cable
- Quick Start Guide
- Utility software bundle (included with select models)

Warranty

- Drives included — 3 year OWC limited, complimentary 1 year Level 1 Data Recovery
- Enclosure only — 1 year OWC limited

Enclosure Dimensions

- 2.8 in (W) x 5.3 in (H) x 8.9 in (D)
- 7.2 cm (W) x 13.5 cm (H) x 22.7 cm (D)

Enclosure Weight (empty)

- 2.5 lb (1.1 kg)

Box Dimensions

- 11.0 in (W) x 4.5 in (H) x 11.5 in (D)
- 27.9 cm (W) x 11.4 cm (H) x 29.2 cm (D)

Box Weight

- 4.0 lb (1.8 kg)

Master Carton Dimensions — 5 pieces

- 12.5 in (W) x 12.4 in (H) x 22.4 in (D)
- 31.8 cm (W) x 31.5 cm (H) x 56.9 cm (D)

Master Carton Weight — 5 pieces

- 22.6 lb (10.3 kg)



PART NUMBER	CAPACITY	UPC	AVAILABLE
OWCTB2U3MED0GB	0GB	812437023961	now
OWCTB2U3MED02T	2.0TB	812437023978	now
OWCTB2U3MED04T	4.0TB	812437023985	now
OWCTB2U3MED04TH	4.0TB Hybrid	812437023992	now
OWCTB2U3MED06T	6.0TB	812437024005	now
OWCTB2U3MED08T	8.0TB	812437024012	now
OWCTB2U3MED10T	10.0TB	812437024029	now
OWCTB2U3MED12T	12.0TB	812437024036	now
OWCTB2U3MED16T	16.0TB	812437024043	now
OWCTB2U3MED20T	20.0TB	812437024050	now



owcdigital.com