

OWC Mercury Elite Pro

20.0TB Multi-Interface External Storage Solution

Mac / PC / USB 3.2 gen 1 / FireWire 800 (FireWire 400 Backwards Compatible) / eSATA



Product Specifications

Specifications

Total Capacity	20.0TB
Standard Mechanism	(j) 20.0TB Western Digital Ultrastar DC HC560 7,200RPM Enterprise Class Hard Disk Drive with 512 MB cache *OWC reserves the right to replace or upgrade to equivalent or better components.
Chipset	JMicron JMB355 / JMicron JMS562
Drive Interface	SATA
Format	Included Drive Guide Software will format drive for either OS X, or Windows
Rotational Speed	7,200RPM
Plug and Play	Yes

Compatibility

Mac OS Compatibility	Mac OS 8.6 Mac OS 9.0 Mac OS 9.1 Mac OS 9.2 Mac OS X 10.0 Cheetah Mac OS X 10.1 Puma Mac OS X 10.2 Jaguar Mac OS X 10.3 Panther Mac OS X 10.4 Tiger Mac OS X 10.5 Leopard Mac OS X 10.6 Snow Leopard Mac OS X 10.7 Lion Mac OS X 10.8 Mountain Lion OS X 10.9 Mavericks OS X 10.10 Yosemite OS X 10.11 El Capitan macOS 10.12 Sierra
PC OS Compatibility	Windows XP Windows XP 64-bit Edition Windows XP Professional x64 Edition Windows Vista Windows 7 32-bit Edition Windows 7 64-bit Edition Windows 8 32-bit Edition Windows 8 64-bit Edition Windows 8.1 32-bit Edition Windows 8.1 64-bit Edition Windows 10 32-bit Edition Windows 10 64-bit Edition Windows 11
Other OS Compatibility	Linux supported via USB and FireWire interfaces
Host Port Requirements	USB (USB-C ¹ or USB-A), Thunderbolt (USB-C) ¹ , eSATA, or FireWire 400/800 port
Other Requirements	Mac OS X 10.2 or later required for FireWire 800 and USB 3.0 Windows 2000 or later required for FireWire 800 and eSATA Time Machine Compatible: Mac OS X 10.5 (version introduced) and later

Power

Power Supply	External UL-listed universal auto-switching power supply
External Power Adapter	Yes

Physical

Number of Bays	1
Device Ports	(1) USB 3.2 Gen 1 Type-B Port (1) eSATA 3 Gb/s Port (2) FireWire 800 Ports
Security Slot	Yes
Power Button	Yes
Power/Activity LED	Yes
Housing Color	Aluminum
Housing Material	Aluminum
Dimensions	Height: 11.7 cm (4.6 in) Length: 22.9 cm (9.0 in) Width: 3.8 cm (1.5 in)
Weight	1.2 kg (2.65 lbs)

Certifications

Certifications	RoHS
-----------------------	------

Environmental

Altitude	Operating: -304.8 m to 3,048.0 m (-1,000 ft to 10,000 ft) Non-Operating: -304.8 m to 12,192.0 m (-1,000 ft to 40,000 ft)
Humidity	Operating: 8% to 90% non-condensing Non-Operating: 5% to 95% non-condensing

Notes

- USB-C (USB or Thunderbolt) host connectivity requires [USB-C to USB-A adapter](#) (available separately)