



Unified Communications  
Microphone & Speaker System

# YVC-1000



## Smart Separation for Closer Communication

Separate microphone and speaker for an intimate audio/video experience



# Effective remote communication through close audio/video integration

The YVC-1000 features separate microphone and speaker units that smoothly integrate audio and video for natural, comfortable remote communication. The high performance, full range speaker unit can be placed close to the display so that audio and video from the remote location blend naturally, while adaptive echo canceller and other Yamaha sound processing technologies facilitate stress-free conversation.



Control unit (with a built-in speaker)

Unified Communications Microphone & Speaker System

**YVC-1000**


Microphone



## A high quality conferencing experience

### Innovative sound processing technologies combine to create a productive communications environment

The YVC-1000 incorporates many high-quality sound technologies that Yamaha has developed over the years, including a unique Human Voice Activity Detection capability used to detect human voices. "HVAD" is an important element of several different sound processing features that require fast and efficient sorting of noise and human voices in order to make speaking and listening a more relaxing, stress-free experience during remote conferencing.






## Flexible connectivity



### Fast, easy connection to PCs, smartphones, tablets, and dedicated conferencing systems

Connect to the YVC-1000 via USB, Bluetooth<sup>\*1</sup>, or the audio terminals<sup>\*2</sup> of a conferencing system for high quality audio in your conferences and meetings. This range of connection options allows you to quickly adapt to a variety of communications environments, as well as situations where conferencing might otherwise be difficult due to the lack of a landline, or internet connectivity issues.

\*1 Supports the mSBC codec for transmission of broadband data.  
\*2 RCA pin plugs.



### Smooth Bluetooth connection using NFC<sup>\*1</sup> technology



Connect simply and easily by placing an NFC-compatible smartphone or tablet over the NFC logo on the top of the control unit while the Bluetooth button is blinking<sup>\*2</sup>.

\*1 NFC may not function correctly with some NFC-compatible devices.  
\*2 If you press the Bluetooth button once, it flashes in blue.



## Excellent scalability

### Connect additional speakers and microphones for larger meetings

In its standard configuration<sup>\*1</sup> the YVC-1000 is ideal for small and medium-size meetings. For conferencing on a larger scale, external speakers<sup>\*2</sup> and up to four additional YVC-MIC1000EX microphones can be added to cover a wider area and accommodate more conference participants.



Up to five microphones can be connected

\*1 The standard YVC-1000 configuration consists of one control unit and one microphone.

\*2 You can connect up to two commercially available powered speakers.





## User-friendly design

### Optimize acoustic settings with a single touch

The YVC-1000 automatically optimizes its acoustic settings by learning about the acoustic environment of a room as it operates. When time requirements mean that speed is an issue, simply pressing the tuning fork button activates the Automatic audio tuning function, immediately optimizing the acoustic settings for your current environment<sup>\*1</sup>. If any acoustic problems are detected, the tuning fork button lights up orange to warn the user. Details on acoustic problems can be accessed through the audio guidance function<sup>\*2</sup>, which also provides announcements for other operations, such as when Bluetooth connections have been established.

<sup>\*1</sup> Automatically measures acoustic characteristics of the operation space and the placement of microphones and speakers, while adjusting the filter settings of the adaptive echo canceller to optimize internal parameters. (This function optimizes settings for the adaptive echo canceller and Automatic room EQ to correct the difference in delay between the internal and external speakers and correct for the frequency characteristics of the external speaker.)

<sup>\*2</sup> Supports English, Japanese, Chinese, Korean, French, Spanish, and German. The default setting is English.




Tuning fork button

## Convenient functions

### Communicate with various sources simultaneously

The audio mixing function mixes multiple voice input sources connected to each interface (USB, Bluetooth, and audio input/output) allowing simultaneous communication over different lines. For example, while connected to a web conference via USB, you can also include more participants via smartphone using a Bluetooth connection by using the audio mixing function to combine the audio sources.



### Connect to an external microphone for more flexibility during remote class sessions or seminars


Equipped with an external microphone<sup>\*1</sup> input, the YVC-1000 is ideal for applications such as remote classes or seminars where a handheld microphone may be preferable. Simply connect an external microphone to output your voice through both the base unit speaker and speakers at remote destinations.

<sup>\*1</sup> Please refer to the website for information on tested handheld microphones.




● Images of sound pickup range (within 3 m (9.8 ft), to a maximum recommended range of 5 m (16.4 ft). \*per microphone)


Microphone x 1




Microphone x 2



Microphone x 3



Microphone x 5



- The sound pickup range may differ depending on the operating environment and conditions.
- Sound quality improves when the person speaking is closer to the microphone.
- For the "Microphone x 3" and "Microphone x 5" configurations shown above, audio quality is superior in the "Microphone x 5" configuration as the microphones are placed closer to the participants.

## Specifications

Unified Communications Microphone & Speaker System  
YVC-1000

General	Interface	Control Unit: USB 2.0 High Speed, Bluetooth, NFC (Near Field Communication) Audio Input terminal (stereo RCA pin), Audio Output terminal (stereo RCA pin), External speaker terminal (RCA pin) x 2, Power terminal, Microphone terminal Microphone: Input and output terminals
	Power consumption (max)	20 W (one connected microphone), 35 W (five connected microphones)
	Radio interference standard	FCC (Part 15B) Class A, ICES-003
	Operating environment	Temperature: 0 to 40°C (32 to 104°F) Humidity: 20 to 85% (no condensation)
	Dimensions	Control Unit (W x H x D): 332 x 95 x 162 mm (13.1 x 3.74 x 6.38 in) Microphone (W x H x D): 136 x 36 x 136 mm (5.35 x 1.42 x 5.35 in)
	Weight	Control Unit: 1.8 kg (4.0 lbs), Microphone: 0.4 kg (0.9 lbs)
	Power source	120 V (60 Hz)
	Supported OS	OS: 32-bit or 64-bit Windows 10, 32-bit or 64-bit Windows 8.1, 32-bit or 64-bit Windows 8, 32-bit or 64-bit Windows 7, Mac OS X 10.11, Mac OS X 10.10, Mac OS X 10.9, Mac OS X 10.8 USB: USB 2.0 or later


General	Bluetooth	Bluetooth specification version: 2.1 + EDR Supported profile: HFP (1.6), A2DP Supported Codec: SBC, mSBC Wireless output: Class 2 Maximum communication distance: 10 m (32.8 ft)
	NFC	Compatible devices: NFC-compatible Android devices, versions 4.1, 4.2, 4.3 and 4.4
	Voice guidance	English, Japanese, Chinese, Korean, French, Spanish, German
	Accessories	Power cable (3 m (9.8 ft)), USB cable (5 m (16.4 ft)), microphone cable (5 m (16.4 ft)), Quick Start Guide
	Others	Firmware update (transfer from PC through USB)
Audio	Microphone unit	Unidirectional x 3
	Speaker unit	Full-range x 1
	Maximum volume	95 dB (0.5 m (1.6 ft))
	Frequency bandwidth	For sound pickup: 100 to 20,000 Hz, For playback: 100 to 20,000 Hz
Signal processing	Adaptive echo canceller, Noise reduction, Automatic tracking, Automatic gain control, Automatic room EQ, Dereverberation, Automatic audio tuning	

### Front

● Control Unit



● Microphone




### Top side

● Control Unit



● Microphone



### Terminals

● Control Unit



- 1 Power terminal
- 2 USB port
- 3 Microphone terminal
- 4 External speaker terminals
- 5 Audio output terminals (AUDIO OUT)
- 6 Audio input terminals (AUDIO IN)

● Microphone



- 7 Input terminal (IN)
- 8 Output terminal (OUT)

## Option

Extension microphone for YVC-1000  
YVC-MIC1000EX



### About trademarks

- Android is a trademark or registered trademarks of Google Inc. ● Bluetooth is a registered trademark of the Bluetooth SIG and is used by Yamaha in accordance with a license agreement.
- NFC logo is a trademark or registered trademark of NFC Forum, Inc.

YAMAHA CORPORATION

<https://uc.yamaha.com/products/yvc-1000/>

© 2019 Yamaha Corporation. All rights reserved.  
Product features and specifications are subject to change without notice by Yamaha.  
All other product and company names and logos that appear in this leaflet are trademarks or registered trademarks of their respective owners.

BR-YVC-1000-20190301-EN